

**2018 ARCTIC CAT ZR200 / YAMAHA SNOSCOOT  
2010 & NEWER YAMAHA SRX 120/ ARCTIC CAT ZR 120  
EXTENDED DIPSTICK KIT Part# NLEDK (rev. 9/17/18)**

1. Remove engine from sled, this will allow you to thread dipstick into block of engine, be careful to keep track of all cables locations for reassembly.
2. Drain oil from engine.
3. Remove plastic dipstick from front of engine.
4. Clean internal threads in crankcase.
5. Install new dipstick as shown, making sure nut is flush with weld on dipstick tube when tightened.

(Apply a small amount of Blue Loctite or Sealant to threads of dipstick tube to help hold tube in place)

6. Fill engine with 18oz of proper oil.

TECH LINE IS AVAILABLE AT (319) 462-6932 MONDAY 9 AM TO 5 PM, TUESDAY AND WEDNESDAY 9 AM TO NOON CENTRAL STANDARD TIME. OR VISIT US AT [www.recmotor.com](http://www.recmotor.com). THANK YOU.

\*\*\*\*\*PLEASE NOTE\*\*\*\*\*  
**This product is intended for closed-course racing only and is sold "as-is" without warranty. Manufacturer and distributor specifically disclaim all responsibility for consequential and incidental damages or any other losses arising from the use of this product. Any dispute arising out of the use of this product must be settled in Linn County, Iowa under Iowa law.**  
\*\*\*\*\*